

AKABA



Gorka Lounge

Wooden waiting room chair

Side structures high-pressure die-cast aluminium. Quality: UNE L-2630. Injection pressure = 1,000 MT.

Shell 9-layer beech wood curved in high frequency hot press and aluminium mould. Surface treatment with fine 100 grade steel wool. Final coat of two-component polyurethane and catalyst with UV and non-yellowing filter. Discontinuous thickness 10-11mm.

Foam cushion with 35 kg/m³ density and 15mm thickness; glued using eco-friendly waterborne adhesive.

Glides polypropylene.


Metallic finishes epoxy/polyester paint with a thickness of 50-90 microns depending on the colour, ISO 2409 Gt 0 adhesion and ASTM 2794 impact 2.5 joules reverse & direct or chrome finish, composition: 98.4% NI, 1.6% CR, 24.4 micron thickness and UNE EN ISO 2409-96 adhesion, Classification 0

Finishes stained with matt acrylic varnish with UV filter available in different options.

Upholstery see manufacturers' specifications.

MEASURES

GORKA LOUNGE



SPECS

**Product weight:**

9,2 kg

**Packaging Information:**

810x690x945 mm

**Number of chairs per box:**

3 Units

**Footage for upholstered versions****(COM):**

(for more than 1 unit contact factory)

0,88 lm / 15 feet

IMAGES



AKABA

Atallu kalea 14
20170 Usurbil (Gipuzkoa)
Spain

akaba@akaba.net
T +34 943 372 211
F +34 943 371 052

© AKABA S.A. All rights reserved