


<b>(Translation) Report No.: 100500-a</b>		Date of receipt: 13.06.2022
		Start date: 29.06.2022
		Date of completion: 19.07.2022
		Issue date: 29.07.2022
		Page 1 of 2
Client:	<b>AKABA, S.A.</b>	
Contact person:	<b>ARKAITZ ARZELUS</b>	
Address:	<b>ATALLU KALEA, 14-16</b>	
	<b>20170 USURBIL (GIPUZKOA) SPAIN</b>	
Reference:	<b>KLASIK (*)</b>	
Characteristics:	<b>Chair with 4 metal legs and plywood seat with armrests and backrest (*)</b>	
Standard:	<b>UNE-EN 16139:2013/Corrected version 2015 (Level L1, general use)</b>	

Test	Standard/Section	Test parameters	RESULT
General safety requirements	UNE-EN 16139:2013/Corrected version 2015 sec.4	---	<b>SATISFACTORY</b>
Safety, strength and durability requirements	UNE-EN 16139:2013/Corrected version 2015 sec.5	---	<b>SATISFACTORY</b>
Front overturn	UNE-EN 1022:2019 sec.7.3.1	Vertical force (N): 600 Horizontal force (N): 20	<b>SATISFACTORY</b>
Backward overturn (chairs with no reclining backrest)	UNE-EN 1022:2019 sec.7.3.6	Vertical force (N): 600 Horizontal force (N): 157,70	<b>SATISFACTORY</b>
Side overturn for chairs with armrests	UNE-EN 1022:2019 sec.7.3.5	Vertical force on seat (N): 250 Vertical force on arm (N): 350 Horizontal force (N): 20	<b>SATISFACTORY</b>
Static load on the seat and backrest	UNE-EN 1728:2013 sec.6.4	Load on seat (N): 1600 Load on back (N): 560 No. of cycles: 10	<b>SATISFACTORY</b>
Static load on the front of the seat	UNE-EN 1728:2013 sec.6.5	Load applied (N): 1300 No. of cycles: 10	<b>SATISFACTORY</b>
Vertical static load on the backrest	UNE-EN 1728:2013 sec.6.6	Force applied (N): 600 Load on seat (N): 1300 No. of cycles: 10	<b>SATISFACTORY</b>
Armrest sideways static load	UNE-EN 1728:2013 sec. 6.10	Load applied (N): 400 No. of cycles: 10	<b>SATISFACTORY</b>
Armrest downwards static load	UNE-EN 1728:2013 sec. 6.11	Load applied (N): 750 No. of cycles: 5	<b>SATISFACTORY</b>
Durability of the seat and the backrest	UNE-EN 1728:2013 sec.6.17	Load on seat (N): 1000 Load on back (N): 300 No. of cycles: 100.000	<b>SATISFACTORY</b>

Test	Standard/Section	Test parameters	RESULT
Durability of the front edge of the seat	UNE-EN 1728:2013 sec.6.18	Load on seat (N): 800 No. of cycles: 50.000	<b>SATISFACTORY</b>
Armrest durability	UNE-EN 1728:2013 sec. 6.20	Force applied (N): 400 No. of cycles: 30.000	<b>SATISFACTORY</b>
Front static load on the legs	UNE-EN 1728:2013 sec.6.15	Force applied (N): 500 Load on seat (N): 1000 No. of cycles: 10	<b>SATISFACTORY</b>
Side static load on the legs	UNE-EN 1728:2013 sec.6.16	Force applied (N): 400 Load on seat (N): 1000 No. of cycles: 10	<b>SATISFACTORY</b>
Seat impact test	UNE-EN 1728:2013 sec.6.24	Drop height (mm): 240 No. of cycles: 10	<b>SATISFACTORY</b>
Backrest impact test	UNE-EN 1728:2013 sec. 6.26	Drop height (mm/ <sup>g</sup> ): 210/38 No. of cycles: 10	<b>SATISFACTORY</b>
Backward drop test, Annex A.2	UNE-EN 1728:2013 sec. 6.28	No. of cycles: 5	<b>SATISFACTORY</b>



Oihana Plazaola  
Technical manager

\*The results obtained in these tests only refer to the sample(s) analysed at this centre on the date shown, and do not involve a sample referring to production quality.  
\*This report will not be able to be reproduced partially without the authorization of TECNALIA.  
\*In case of a lawsuit, the original Spanish report shall be taken as reference  
(\*) Information provided by the customer. Tecnalia is not responsible for the information provided by the customer.